



SUPERLUBE-HYD 68

HYDRAULIC & CIRCULATING OIL-ANTIWEAR TYPE

Hydraulic oil designed for use in circulating systems is made for high viscosity index. Chemically stable base stocks which are further added with additives like antioxidants, anticorrosive, antiwear & antifoam. They meet the requirement of very high pressure systems & also with high pump speeds.

SUPERLUBE-HYD 68 PASSES FOLLOWING CHARACTERISTICS

- High viscosity index to restrict viscosity changes under operating conditions.
- Good film strength and antiwear properties to minimize wear of pumps, valves, cylinders and pistons etc.
- Right viscosity to satisfy the demands of the hydraulic pump and the system.

PRODUCT SPECIFICATION

PROPERTIES	SUPERLUBE-HY 68
Viscosity @ 40 ^o C cST	68
Viscosity Index	95
Flash Point COC ^o C	205
Pour Point ^o C	-6
Neutralisation Number (mg KOH / gm)	1.5



Pratap Tex-Chem Pvt. Ltd.

Pune Office & Works :

S. No. 25/5, Nanded Phata, Sinhgad Road, Pune - 411 041.

Tel. : 020 - 65706584, 65701569. Telefax : 020 - 24391569

E-mail : prataptech@vsnl.net / prataptex@bsnl.in Web : www.pratapchem.com

AN ISO 9001:2000 registered Company

The information contained in this literature is true to the best of our knowledge but without warranty



DEALERS AT :